


Lifting stati. Aqualift F XL 300l Duo, SPF 3000-S3, shut-off valve



Article information

Item no.: 11048
GTIN: 4026092057155
Price group: 50

Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

Variant

| | |
|---------------------------------------------|--------------------------------|
| Type of system: | duo pump |
| Shut-off valve: | Shut-off valve made of polymer |
| Retaining bracket for the lift protection: | yes |
| Tested sound insulation as per test report: | yes |
| Rim width: | Control unit |
| Backwater protection: | integrated |
| Pressure pipe connection: | horizontal |

General characteristics

| | |
|-------------------------|----------------------------------------------------------------------------------------|
| Colour: | black |
| Standard: | EN 12050-1 |
| Type of wastewater: | with sewage |
| Installation situation: | free-standing installation |
| Delivery state: | Installation-ready (electrical components, connection parts must be connected on site) |
| System type: | Duo |

Dimensions

| | |
|----------------------|-----------|
| Net weight: | 109,59 kg |
| Gross weight: | 129,59 kg |
| Length: | 1260 mm |
| Width: | 760 mm |
| Height: | 806 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

Tank/drain body

| | |
|-----------------------------------------------------|--------|
| Pressure pipe connection (DN): | 100 |
| Pressure pipe connection (OD): | 110 mm |
| Connection for manual diaphragm pump (DN): | 32 |
| Venting connection (DN): | 70 |
| Distance from centre of outlet pipe to tank bottom: | 609 mm |
| Number of inlets: | 200 mm |
| Inlet nominal size (DN): | 110 mm |
| Inlet nominal size (DN): | 100 mm |
| Inlet type: | 1 |
| Pumping volume: | 175 l |
| Tank volume: | 300 l |

Pumping device

| | |
|----------------------------------------------------|--------------------------------|
| Pump control: | SPF 3000 |
| Number of pumps: | 2 |
| Weight: | 24 kg |
| Connection type: | Direct connection |
| Rated current: | 5,4 A |
| Length of mains cable for pump: | 5 m |
| Self-diagnosis system (SDS): | I |
| Insulation class: | F |
| Cos phi - power factor: | 0,89 |
| Protection class control unit: | IP 68 (3m/48h) |
| DSC: | integrated |
| Max. temperature (permanent) of conveyed material: | 40 °C |
| Max. pumping capacity: | 47 m ³ /h |
| Max. pumping height: | 16 m |
| Speed: | 2845 U/min |
| Power P1: | 3,2 kW |
| Power P2: | 2,7 kW |
| Operating mode: | S3 - 50 % |
| Type of pump connection cable: | H07RN-F 7G 1.5 mm ² |
| Impeller type: | Multi-vane impeller |
| Free passage: | 40 mm |

Control

| | |
|---------------|---------|
| Control unit: | Comfort |
|---------------|---------|

| | |
|-------------------------------|-------------------|
| Motor protection switch: | yes |
| Alarm sensor: | Immersion pipe |
| Level measurement instrument: | Immersion pipe |
| Type of level measurement: | pneumatic |
| Protection class probe: | IP 54 |
| Operating voltage: | 400 V |
| Connection type: | Direct connection |
| Potential-free contact: | yes |
| GSM interface: | yes |
| Log book function: | yes |
| Multi-line display: | yes |
| Battery buffering: | yes |
| Self-diagnosis system (SDS): | yes |
| Rated current: | 5,4 A |