

Basement drain DN 100, Black grating, Class K 3



Article information

Item no.: 29111
 GTIN: 4026092007846
 Price group: 10

Advantages

- Integrated odour trap
- Including sludge bucket

Description

The basement drain made of polymer for floor slab installation is equipped with an odour trap and a sludge bucket. The upper section with slotted grating is vertically adjustable.

Variant

Contents of sludge trap:	yes
Position of lateral connection:	Type II
Sealing water height:	60 mm
Discharge rate (l/s) with 20 mm backwater:	1,8

General characteristics

Standard:	EN 1253-1
Nominal size (DN):	100
Outer diameter (OD):	110 mm

Dimensions

Vertical adjustment:	30 - 90 mm
Net weight:	2,55 kg
Gross weight:	2,88 kg
Cutout dimension, width:	320 mm
Cutout dimension, length:	400 mm
Installation depth:	216 - 276 mm
Vertical adjustment:	vertically adjustable upper section
Length:	380 mm
Width:	290 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body

Inlet nominal size (DN):	70 mm
Inlet type:	2

Material of drain body:	PP
System:	lateral
Coverage features	
Type of cover:	Slotted cover
Cover material:	Polymer
Colour of cover:	black
Width of cover:	188 mm
Length of cover:	188 mm
Frame material:	Polymer
Cover locking:	placed
Load class:	K 3 (EN 1253-1)
Rim length:	200 mm
Rim material:	200 mm
Upper section material:	Polymer
Contents of sludge trap:	yes
Odour trap:	included