


## The Ultraflat 79 floor drain DN 50, Slotted grating



### Article information

Item no.: 44700.20  
 GTIN: 4026092080900  
 Price group: 10

### Advantages

- Low installation depth
- Scientifically confirmed sound insulation effect
- different design covers

### Description

The Ultraflat 79 floor drain is suitable for indoor floor drainage. The polymer drain is equipped with a removable odour trap in the upper section.

Variant	
System:	125
SonicControl:	optional
Sealing water height:	50 mm
General characteristics	
Standard:	EN 1253-1
Nominal size (DN):	50
Outer diameter (OD):	50 mm
Dimensions	
Vertical adjustment:	88 - 139 mm
Net weight:	0,51 kg
Gross weight:	0,66 kg
Vertical adjustment:	vertically adjustable upper section
Length:	227 mm
Width:	163 mm
Height:	79 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body	
Number of outlets:	1
Material of drain body:	ABS
System:	lateral
Coverage features	
Type of cover:	Slotted cover
Cover material:	Stainless steel 14301
Colour of cover:	silver
Width of cover:	120 mm
Height of cover:	16 mm
Length of cover:	120 mm
Surface:	Polished SST
Frame material:	ABS
Cover locking:	unlocked
Load class:	K 3 (EN 1253-1)
Slip resistance class:	R9 according to DIN 51130; C according to DIN 51097
Rim length:	130 mm
Rim material:	130 mm
Shape of upper section:	square
Upper section material:	ABS
Odour trap:	included